



PERFORMANCE

| 720 cased pumps' performance limits | | | | | | | | | | |
|-------------------------------------|-------------------|---------------------|------------------|---------------------|------------------|---------------------|------------------|---------------------|------------------|---------------------|
| Single pumphead (720R, 720RE) | 0.25 bar (3.6psi) | | 0.5 bar (8psi) | | 1 bar (15psi) | | 1.5 bar (22psi) | | 2 bar (30psi) | |
| | Max speed (rpm)* | Max flow | Max speed (rpm)* | Max flow | Max speed (rpm)* | Max flow | Max speed (rpm)* | Max flow | Max speed (rpm)* | Max flow |
| 9.6mm (0.4") | 360 | 420 L/hr (111 GPH) | 360 | 420 L/hr (111 GPH) | 360 | 420 L/hr (111 GPH) | 360 | 420 L/hr (111 GPH) | 360 | 420 L/hr (111 GPH) |
| 12.7mm (0.5") | 360 | 780 L/hr (206 GPH) | 360 | 780 L/hr (206 GPH) | 360 | 780 L/hr (206 GPH) | 360 | 780 L/hr (206 GPH) | 360 | 780 L/hr (206 GPH) |
| 15.9mm (0.6") | 360 | 1100 L/hr (291 GPH) | 360 | 1100 L/hr (291 GPH) | 360 | 1100 L/hr (291 GPH) | 360 | 1100 L/hr (291 GPH) | 300 | 900 L/hr (238 GPH) |
| 19.0mm (0.7") | 360 | 1500 L/hr (396 GPH) | 360 | 1500 L/hr (396 GPH) | 360 | 1500 L/hr (396 GPH) | 300 | 1300 L/hr (343 GPH) | 250 | 1000 L/hr (264 GPH) |
| 25.4mm (1.0") | 360 | 2000 L/hr (528 GPH) | 360 | 2000 L/hr (528 GPH) | 360 | 2000 L/hr (528 GPH) | 200 | 1100 L/hr (291 GPH) | | |

*The maximum speed is reduced at increased discharge pressures to ensure safe running of the pump



SPECIFICATIONS

| 720SN, 720UN, 720DuN | |
|----------------------|---|
| Ingress rating | IP66 / NEMA 4X |
| Enclosure | Watertight / dustproof |
| Suitability | Corrosion resistant for heavy industrial environments |
| Humidity | Condensing 10-100% RH |
| Temperature | 5C to 40C (40F to 104F) |
| Pump weight | 25kg (55lb) with 720RE, 31.5kg (69lb) with 720REX |
| Control ratio | 3,600:1 |
| Torque rating | Max 2.5Nm (shaft, x 4 at pumphead) |
| Noise | < 85dB(A) at 1m |
| Standard | CE, cETLus |
| Power supply | 100-120V/200-240V 1ph 50/60Hz, 350vA |

MATERIALS OF CONSTRUCTION

| Component | Material |
|-------------------------------|---|
| Keypad | Polyester |
| Switch-plate | ABS PA-765 |
| Rear blanking plate | Stainless steel 316 |
| Drive casework | Pressure die-cast aluminium (top - LM6, base - LM24) |
| Casework and pumphead coating | Alocrom pre-treatment, exterior grade polyester powder coat |
| Drive shaft | Stainless steel 440C |
| Pumphead body/track | Aluminium |
| Rotor end plates | Aluminium |
| Rollers | MOS2 filled nylon 6 (Nylatron) |
| Springs/spindles | Stainless steel |

ORDER INFORMATION

| Product codes | | | |
|---------------|---------------|---------------------|--------------|
| Description | Partcode | Description | Partcode |
| 720SN/RE | 070.413N.E00* | 720RE pumphead only | 073.2004.000 |
| 720UN/RE | 070.414N.E00* | | |
| 720DuN/RE | 070.415N.E00* | | |
| Leak detector | 079.6131.E00 | | |

*Replace 0 (plug-less) with A for American mains lead, K for Australian mains lead and R for Argentinian mains lead

| | LoadSure Industrial elements 3/4" Cam & Groove PP connectors | | | | 1" Cam & Groove PP connectors | LoadSure Sanitary elements 3/4" Tri-clamp style PVDF connectors | | | 1" Tri-clamp style PVDF connectors |
|--------------|---|--------------|--------------|--------------|-------------------------------|--|--------------|--------------|------------------------------------|
| | 12.7mm | 15.9mm | 19.0mm | 25.4mm | | 12.7mm | 15.9mm | 19.0mm | |
| Marprene | 902.0127.PPC | 902.0159.PPC | 902.0190.PPC | 902.0254.PPC | | | | | |
| Pumpsil | 913.A127.PPC | 913.A159.PPC | 913.A190.PPC | 913.A254.PPC | 913.A127.PFT | 913.A159.PFT | 913.A190.PFT | 913.A254.PFT | |
| Neoprene | 920.0127.PPC | 920.0159.PPC | 920.0190.PPC | 920.0254.PPC | | | | | |
| Bioprene | | | | | 903.0127.PFT | 903.0159.PFT | 903.0190.PFT | 903.0254.PFT | |
| STA-PURE PCS | | | | | 960.0127.PFT | 960.0159.PFT | 960.0190.PFT | 960.0254.PFT | |

All flow rates shown were obtained pumping water at 20C (68F) with zero suction and delivery heads. Watson-Marlow, Bioprene and Marprene are trademarks of Watson-Marlow Limited. Disclaimer: The information contained in this document is believed to be correct but Watson-Marlow Limited accepts no liability for any errors it contains, and reserves the right to alter specifications without notice. LoadSure is a trademark of Watson-Marlow Limited. © STA-PURE PFL and © STA-PURE PCS are registered trademarks of W.L Gore & Associates Inc. Please state the product code when ordering pumps and tubing.

**WATSON
MARLOW
Pumps**

wmftg.co.uk
info@wmftg.co.uk
+44 (0) 1326 370370